



Makefast

Marine Products

Powered Sun Awning System

Technical specification

- Low profile system designed to fit invisibly within the structure of the boat.
- Rigid 316 SS construction with spring loaded arms for a taut canvas.
- Horizontally mounted from above or below depending on the design of boat.
- Maximum extension of 2.2 mtr (7.2') with 316 SS arms.
- Larger extension available with Carbon fibre arms (dependent on boat design).
- Maximum width of 4 mtr (13').
- Quick release 316 SS support struts available for securing the awning to the deck when deployed.
- 12 or 24 volt systems with soft start & soft stop, electrical overload safety trip, plug & play connections & a manual override.
- Swela sunsilk anti fungal canvas.
- 316 SS front valance rail designed to match curvature of the boat & can be clad with GRP or Carbon fibre trim if required.
- 2 year warranty period from date of dispatch (full details available on request).



For enquiries please call our technical sales team on: UK: +44 (0)1686 629010

or visit: www.makefast.com



Makefast

Marine Products

Powered Sun Awning System

Dimension	Value
A	Up to 4000mm [157"]
B	Up to 2500mm [98.4"]
C	Dim. A + 54mm [2.1"]
D	Dim. A + 275mm [10.8"]

If awning extension is <1600mm the awning may be used without support stanchions. However it is still advised that the awning is not left deployed during motion and windy weather.

Date: 02/12/2014 Drawn by: H.Kommers
 Scale: 1:50 A3
 All dimensions in mm unless otherwise stated
 Do not scale
 31 Mochdre Industrial Estate
 Newtown Powys
 SY16 4LE
 Tel: 01686 629010
 Fax: 01686 626700
 Design Copyright Makefast Ltd

GRP
 M10-A4 Mounting Bolts
 Mounting Bracket
 10mm Thick (Minimum) steel fixing plate Laminated into GRP

SUSPENDED MOUNTING

CROSS SECTIONS THROUGH MOUNTING BRACKETS TO SHOW TYPICAL FIXING METHODS

SUPPORTED MOUNTING

For enquiries please call our technical sales team on: UK: +44 (0)1686 629010

or visit: www.makefast.com