

# Pump Accumulator Kit – Integrated

**Smooth constant flow - prevents water hammering and cycling.  
One piece kit includes pump and compact accumulator tank**

This integrated kit is a drop into line pre-assembled kit designed to provide a constant reliable flow of water on board. Save time and money with this quick to install pre-assembled kit

Easy maintenance inlet strainer with clear lid for inspection prevents debris from entering the pump

Accumulator tank combines high capacity and compact size

UF2015

Easy installation pre-mounted kit 4 screws and connect plumbing

Moulded base drop in and fit one piece kit

Connects directly to 15 mm Quick Connect pipework. Suitable to connect to 1/2" flexible hose or 3/8" flexible hose with Whale adaptors (see specifications)



UF2215

# Combined Pump And Accumulator Tank Ensures A Smooth Even Flow Of Water To All Outlets

- Combined pump and accumulator tank ensures a smooth even flow of water to all outlets
- Compact design installs easily in convenient locations
- Reduced noise and vibration by preventing pump cycling
- Easily plumbed into standard 1/2" or 3/8" pipework
- Connects directly to Whale Quick Connect 15 mm plumbing system
- Can be fitted to new or existing systems
- Includes long life Whale pressure pump

## 2 Year Warranty

## Approvals and Standards

- EMC compliant
- CE marked

## COMPLETE YOUR SYSTEM

Freshwater system accessories such as water filters, and pipework connections - page 68

## YOU MAY ALSO LIKE

Whale Quick Connect plumbing - Pipework and fittings - page 82-85

## TANKS ALSO AVAILABLE

PT0200 - 2 ltr (0.53 US Gal) capacity tank also available separately



## i Product Information

### Model Specifications

Model	Accumulator Kits					
<b>Product Code</b>	<b>UF2214</b>	<b>UF2215</b>	<b>UF2224</b>	<b>UF2225</b>	<b>UF2015</b>	<b>UF8025</b>
Includes Pressure Pump Model	UF1214	UF1215	UF1224	UF1225	UF1215	UF1825
Accumulator Tank Size	2 ltrs (0.53 US Gals)				8 ltrs (4.75 US Gals)	
Open Flow Rate per Minute	11.5 ltrs (3.0 US Gals)				12 ltrs (3.2 US gals)	18 ltrs (4.75 US gals)
Voltage	12 V d.c.		24 V d.c.		12 V d.c.	24 V d.c.
Recommended Fuse Size	10 A		5A		8A	8A
Cut Out Pressure	2 bar (30psi)	3 bar (45psi)	2 bar (30psi)	3 bar (45psi)	2 bar (30psi)	3 bar (45psi)
Weight	3.9kg				5.4 kg	5.9 kg
Factory Pre-charge Pressure (+/-0.014 bar+/-2psi)	1.5 bar (22 psi)	2.2 bar (32psi)	1.5 bar (22 psi)	2.2 bar (32psi)	1.4 bar (20 psi)	2.2 bar (32psi)
Inlet / Outlet Connections	Quick Connect Whale® 15 mm connections				Whale Quick Connect 15 mm Female For 1/2" Flexible Hose, Use WX1584 (supplied with kit) For 3/8" Flexible Hose, Use WU1215 and WU1280 (not supplied with kit)	
Materials	Pump Body: Glass-filled Polypropylene Aluminium and Powder-coated Steel Diaphragms: antoprene, Valves and Feet: Monoprene®, Seals: Nitrile®, Tank: Butyl, Base: ABS Fittings: Brass, Fasteners: Stainless Steel					
Materials in Contact With Fluid	Glass-filled Polypropylene, Monprene®, Nitrile®, Stainless Steel, Brass					
Minimum Wire Size	2.5 mm (20 SWG)					
Maximum Discharge Head	3 m (10 ft)					
Maximum Suction Lift	20 m (66 ft)	30 m (99 ft)	20 m (66 ft)	30 m (99 ft)	20 m (66 ft)	30 m (99 ft)

Note: These specifications are retail items only.

For details of our bulk pack range for boat builders and wholesalers - contact Whale Support.

